

# DUROCURING

## waterbased concrete curing liquid

**DUROCURING** is a ready to use impregnating liquid that provides efficient curing and protection against drying for new floors constructed from plain concrete or with dry shakes surface hardeners.

### AREAS OF USE

- Industrial floors
- Monolithic concretes
- Indoor and outdoor concrete surfaces
- Cement based repair materials

### FEATURES

- Easy to apply
- Eliminates dusting on concrete floor surfaces
- Ensures homogeneous, appropriate drying
- Limits the effects of cracking
- Can be applied to smooth or rough surfaces
- **DUROCURING** treated concrete floors are suitable for concrete paint, resin or ceramic coating
- Does not include silicone or any material, which could diminishes the attachment of new layer application
- Milk-white liquid

### APPLICATION

**DUROCURING** should be spray applied to the surface of concrete immediately after the finishing operations.

### USE OF MATERIAL

The quantity of **DUROCURING** used is highly dependent from weather conditions and the porosity of the concrete surface. In general, 0,1 liter of curing liquid needs to be applied on a 1 m<sup>2</sup> surface. The suggested quantity should not be exceeded, because the excess material cannot blend into the surface and will create a yellowish white, wax-like coat on top of the surface. Though, this layer can be cleaned by mechanical cleaning.

### PACKAGING

**DUROCURING** is supplied in 20, 60, 120 liter drums.

### STORAGE

Store in cool, but frost-free conditions.  
Shelf life: 12 months.

### SAFETY PRECAUTIONS

Water based product. Protect against freezing. Frozen product cannot be installed. Non-hazardous product.

