

DUROSEAL

solvent-based curing liquid

DUROSEAL is a ready to use impregnating, surface curing liquid, which provides an outstanding protection for the fresh concrete as well as for the dry shake hardener treated industrial floors against drying. It can also be utilized for impregnating stone coatings.

AREAS OF USE

- Industrial floors
- Colored surfaces
- Monolith concretes
- External and internal concrete surfaces
- Cement slurries, plasters

FEATURES

- Homogeneous, shiny surface
- Easy application
- Stops surface porosity
- Ensures proper and even drying process
- Reduces cracking
- Can be used on smooth and uneven surfaces
- Non-colored liquid with aroma odor
- Density: 0.85
- Dry Material content: approx. 15%

INSTALLATION

DUROSEAL is a ready to use product and must not be thinned with solvents. Stir up before use. The **DUROSEAL** needs to be applied with a sprayer. In case of surface hardened industrial floors, special care is required not have an overly wet floor. Sprayer cleaning: synthetic thinner. First time use: 6 hours at 20°C and 12 hours at 5°C.

MATERIAL REQUIREMENTS

The **DUROSEAL** material requirement depends on weather circumstances and the porosity of the concrete surface.

In general, for 1m² surface 80-150 g curing liquid should be applied. Avoid overdosing, because it creates a wax-like layer, which is hard to remove from the concrete surface.

PACKAGING

1000 liter containers. If demanded 20 liter barrels.

STORAGE

Can be stored up to 24 months in a cool, dry environment, if the original, unopened packaging remains. Frost safe.

SAFETY PRECAUTIONS

Danger level: Xn hazardous

Flammable level: B II.

Flammable and explosive.

The details of specifications can be found on the product label. For more information ask for the product safety data sheet.

