

# LIQUI-HARD

## concrete surface compacting and reinforcing liquid

**LIQUI-HARD** is a ready-to-use, transparent liquid, which by penetrating deeply into concrete floors will cure, compact and strengthen the concrete through a combined chemical-moisture retention reaction. Floors treated with **LIQUI-HARD** have increased abrasion resistance and resist several chemicals. It is exceptionally useful against corrosion and protection of concrete floors with metal particles.

### AREAS OF USE

- Industrial concrete floors
- Monolithic concretes
- Indoor and outdoor slabs
- Cement based correction materials

### TECHNICAL FEATURES

- Increases the surface's shock and abrasion resistance
- Creates resistance against several chemicals
- Completely isolates pores
- Transparent material, it does not change the color of the base surface

### INSTALLATION

Installation and finishing process is 60-90 minutes. Tools required for installation: soft sweeper, rubber broom or wet vacuum cleaner. During installation, continuous water supply must be available. The installation must be carried out by the installation manual.

### USE OF MATERIAL

0,1-0,2 liter/m<sup>2</sup>, depending on the porosity of the floor.

### TEMPERATURE LIMITS

It can be applied between +2°C and +57°C.

### FIRST TIME USE

2-4 hours after installation. In regards to loading of the floor, please follow the guidelines of the concrete floor itself.

The floor can be painted or extra layer can be applied after 3-7 days from installation.

### SAFETY PRECAUTIONS

Water based liquid. Non-toxic, environment friendly product. Please avoid contact with eyes.

Non-flammable. Glass and metal surfaces must be protected during installation.

### PACKAGING

Supplied in 208 liter drums.

### STORAGE

1 year in original packaging. Stir up before use.

